K-SPIR SCHL KUPPL SET STANDARD

Spiral hose and coupling kit with standard coupling

Свойства

Применение	Air, gases, oils, greases, fuels, organic and inorganic substances
Рабочая температура	-40 °C to +100 °C
Вид подключения	connection nipples and coupling NW 7,2



Указание

Прочие данные только по запросу.

Описание

These hoses allow gaseous and liquid media to flow safely and efficiently (Air, gases, oils, greases, fuels, organic and inorganic substances). Thanks to their small coil diameter, they are compact, easy to handle and lightweight. Very good recoil force owing to the use of nylon 12 (PA).

Изделие

Наименование	Внутренний Ø шланга (mm)	Внешний Ø шланга (mm)	Внешний Ø спирали (mm)	Витки	Max. working pressure resistance at 23°C (bar)	макс. рабочая длина (m)
K- 07 10 12 95	6,3	7,9	75	15	13	2,5
K- 07 10 12 96	6,3	7,9	75	30	13	5,0
K- 07 10 12 97	6,3	7,9	75	45	13	7,5
K- 07 10 12 65	7,9	9,5	115	10	12	2,5
K- 07 10 12 66	7,9	9,5	115	20	12	5,0
K- 07 10 12 67	7,9	9,5	115	30	12	7,5
K- 07 10 12 68	9,5	11,8	140	8	11	2,5
K- 07 10 12 69	9,5	11,8	140	15	11	5,0
K- 07 10 12 70	9,5	11,8	140	23	11	7,5

Принадлежности

K-DREHBARE VERSCHR KNICK	Swivel adapters with kink protector
K-STARRE VERSCHRAUBUNG	Rigid adapters with kink protector

Несмотря на тщательную проверку мы не может исключить ошибки, поэтому мы не берем на себя ответственность за содержащуюся информацию.