

K-SPIR SCHL KUPPL SET LKM NW 7,4

Spiral hose and coupling kit with pushbutton-type safety coupling (DN 7.4) and push-in plug, galvanised steel

HANSA FLEX

Свойства

| | |
|---------------------|--|
| Вид подключения | with pushbutton safety coupling NW 7,4 steel nipple galvanised |
| Рабочая температура | -40 °C to +74 °C |



Указание

Прочие данные только по запросу.

Описание

Standard type or with braided reinforcements for high pressures. These exceptionally elastic polyurethane hoses boast a recoil force similar to that of conventional nylon spiral hose, but with less tendency to loop and significantly better resistance to abrasion. There is consequently less danger of scratching coated or sensitive surfaces. The hose is extremely flexible and non-kinking.

Не предназначено для ударных или перфорационных инструментов!

Изделие

| Наименование | Внутренний Ø шланга (mm) | Внешний Ø шланга (mm) | Ø внешнего витка (mm) | Max. working pressure resistance at 23° C (bar) | макс. рабочая длина (m) |
|----------------|-----------------------------|--------------------------|--------------------------|---|----------------------------|
| K- 07 10 12 71 | 5,0 | 8,0 | 40 | 10 | 3,0 |
| K- 07 10 12 73 | 5,0 | 8,0 | 40 | 10 | 6,0 |
| K- 07 10 12 75 | 5,0 | 8,0 | 40 | 10 | 7,5 |
| K- 07 10 12 80 | 6,3 | 9,5 | 60 | 10 | 3,0 |
| K- 07 10 12 82 | 6,3 | 9,5 | 60 | 10 | 6,0 |
| K- 07 10 12 84 | 6,3 | 9,5 | 60 | 10 | 7,5 |
| K- 07 10 12 78 | 6,3 | 9,5 | 60 | 10 | 10,0 |
| K- 07 10 12 89 | 8,0 | 12,0 | 80 | 9 | 3,0 |
| K- 07 10 12 91 | 8,0 | 12,0 | 80 | 9 | 6,0 |
| K- 07 10 12 93 | 8,0 | 12,0 | 80 | 9 | 7,5 |
| K- 07 10 12 87 | 8,0 | 12,0 | 80 | 9 | 10,0 |

Принадлежности

K-DRENBARE VERSCHRAUBUNG Swivel adapters