

K-WERKST-SCHLAUCH SOFT O

Workshop hose soft, oil resistant

HANSA FLEX

Свойства

Внутренний слой	Soft-PVC, red, oil resistant
Вставка	Оплетка из полиэфира
Наружный слой	Soft-PVC, black, oil resistant
Температура	-20 °C to +60 °C
Длина рулона	50 m



Указание

Прочие данные только по запросу.

Описание

Workshop hose to meet the most demanding requirements. Extremely flexible (even at low temperatures), good resistance to oil and chemicals, long service life and excellent resistance to mechanical stresses (deformation under pressure, bending cycles, pressure pulses).

Изделие

Наименование	Внутренний Ø шланга (mm)	Внешний Ø шланга (mm)	Max. working pressure resistance at 23°C (bar)	Мин. радиус изгиба (mm)
K- 07 10 10 41	6,3	11,0	16	18
K- 07 10 10 42	8,0	13,0	16	25
K- 07 10 10 43	9,0	14,5	16	25
K- 07 10 10 44	10,0	15,5	16	35
K- 07 10 10 45	12,7	19,0	16	50
K- 07 10 10 46	16,0	23,0	16	70
K- 07 10 10 47	19,0	26,5	16	70
K- 07 10 10 48	25,0	33,5	16	120