

K-KOMPAKTZYL SCHWENKTISCH MSQ

Rotary actuator for compact cylinder MSQ

HANSA FLEX

Свойства	
Макс. рабочее давление	0,7 MPa
мин. рабочее давление	0.10 MPa
Исполнение	rack and pinion
Температура среды	0 °C to +60 °C
Температура окружающей среды	0 °C to +60 °C
Угол качания	0 to 190°
Рабочие среды	Сжатый воздух
Серия	MSQ
Прочие данные	narrow pivot table unit with low overall height the rotation angle can be adjusted continuously Positioning the housing allow for quick installation the load can be mounted directly on the pivot table Air connections of 2 pages possible



Изделие						
Наименование	Ø поршня (mm)	Соединение пневматическое	Типоразмер	Гашение	Вес на м (kg)	
K- 07 55 01 13	6	M 3	1	without, with adjustment bolt	0,075	
K- 07 55 01 18	8	M 5	2	without, with adjustment bolt	0,105	
K- 07 55 01 21	10	M 5	3	elastic, with adjustment bolt	0,150	
K- 07 55 01 26	12	M 5	7	elastic, with adjustment bolt	0,250	
K- 07 55 01 11	15	M 5	10	elastic, with adjustment bolt	0,530	
K- 07 55 01 16	18	M 5	20	elastic, with adjustment bolt	0,990	
K- 07 55 01 19	21	G 1/8	30	elastic, with adjustment bolt	1,290	
K- 07 55 01 22	25	G 1/8	50	elastic, with adjustment bolt	2,080	
K- 07 55 01 24	28	G 1/8	70	elastic, with adjustment bolt	2,880	
K- 07 55 01 09	32	G 1/8	100	elastic, with adjustment bolt	4,090	
K- 07 55 01 14	40	G 1/8	200	elastic, with adjustment bolt	7,580	
K- 07 55 01 12	15	M 5	10	elastic, with integrated shock absorber	0,540	
K- 07 55 01 17	18	M 5	20	elastic, with integrated shock absorber	0,990	
K- 07 55 01 20	21	G 1/8	30	elastic, with integrated shock absorber	1,290	
K- 07 55 01 23	25	G 1/8	50	elastic, with integrated shock absorber	2,100	
K- 07 55 01 25	28	G 1/8	70	elastic, with integrated shock absorber	2,880	
K- 07 55 01 10	32	G 1/8	100	elastic, with integrated shock absorber	4,100	
K- 07 55 01 15	40	G 1/8	200	elastic, with integrated shock absorber	7,650	