

K-W90 DRV AS-FS

Speed controllers, 90°, connection plug, with built-in indicator

HANSA FLEX

| Свойства | |
|------------------------------|---|
| Макс. рабочее давление | 1 MPa |
| мин. рабочее давление | 0.10 MPa |
| Отводы | 1 |
| Количество питающих линий | 1 |
| Выравнивание окна индикатора | 0° |
| Ручка настройки цвета | Blue |
| Испытательное давление | 1,50 MPa |
| Управление | Flow governing |
| Температура среды | -5 °C to +60 °C (ohne Gefrieren) |
| Температура окружающей среды | -5 °C bis +60 °C (no freezing) |
| Рабочие среды | Сжатый воздух |
| Материал шланга | polyamid, soft polyamid, polyurethane, FEP, PFA |
| Серия | AS-FS |
| Прочие данные | large rotary knob with push-lock latch larger free space under the hose Lockable rotary knob, numeric display |



| Изделие | | | | | | |
|----------------|------------|----------------------------|---------------------------|---------------------------|--------------|---------------|
| Наименование | Типоразмер | Соединение отводящей линии | Соединение питающей линии | Исполнение | Обороты иглы | Вес на м (kg) |
| K- 07 30 30 54 | 1 | for hose outer-Ø2 mm | outer thread M 5 | with sealing ring | 8 | 0,007 |
| K- 07 30 30 57 | 1 | for hose outer-Ø3.2 mm | outer thread M 5 | with sealing ring | 8 | 0,007 |
| K- 07 30 30 55 | 1 | for hose outer-Ø4 mm | outer thread M 5 | with sealing ring | 8 | 0,007 |
| K- 07 30 30 56 | 1 | for hose outer-Ø6 mm | outer thread M 5 | with sealing ring | 8 | 0,008 |
| K- 07 30 30 62 | 2 | for hose outer-Ø3.2 mm | outer thread R 1/8 | Teflon coated | 10 | 0,007 |
| K- 07 30 30 67 | 2 | for hose outer-Ø3.2 mm | outer thread R 1/4 | Teflon coated | 10 | 0,023 |
| K- 07 30 30 58 | 2 | for hose outer-Ø4 mm | outer thread R 1/8 | Teflon coated | 10 | 0,013 |
| K- 07 30 30 63 | 2 | for hose outer-Ø4 mm | outer thread R 1/4 | Teflon coated | 10 | 0,023 |
| K- 07 30 30 59 | 2 | for hose outer-Ø6 mm | outer thread R 1/8 | Teflon coated | 10 | 0,014 |
| K- 07 30 30 68 | 2 | for hose outer-Ø6 mm | outer thread G 1/8 | surface with sealing ring | 10 | 0,014 |
| K- 07 30 30 64 | 2 | for hose outer-Ø6 mm | outer thread R 1/4 | Teflon coated | 10 | 0,023 |
| K- 07 30 30 69 | 2 | for hose outer-Ø6 mm | outer thread G 1/4 | surface with sealing ring | 10 | 0,023 |
| K- 07 30 30 60 | 2 | for hose outer-Ø8 mm | outer thread R 1/8 | Teflon coated | 10 | 0,015 |
| K- 07 30 30 65 | 2 | for hose outer-Ø8 mm | outer thread R 1/4 | Teflon coated | 10 | 0,024 |
| K- 07 30 30 70 | 2 | for hose outer-Ø8 mm | outer thread G 1/4 | surface with sealing ring | 10 | 0,024 |
| K- 07 30 30 61 | 2 | for hose outer-Ø10 mm | outer thread R 1/8 | Teflon coated | 10 | 0,016 |
| K- 07 30 30 66 | 2 | for hose outer-Ø10 mm | outer thread R 1/4 | Teflon coated | 10 | 0,025 |
| K- 07 30 30 71 | 2 | for hose outer-Ø10 mm | outer thread G 1/4 | surface with sealing ring | 10 | 0,025 |
| K- 07 30 30 72 | 3 | for hose outer-Ø6 mm | outer thread R 3/8 | Teflon coated | 10 | 0,038 |
| K- 07 30 30 76 | 3 | for hose outer-Ø6 mm | outer thread G 3/8 | surface with sealing ring | 10 | 0,038 |
| K- 07 30 30 73 | 3 | for hose outer-Ø8 mm | outer thread R 3/8 | Teflon coated | 10 | 0,038 |
| K- 07 30 30 77 | 3 | for hose outer-Ø8 mm | outer thread G 3/8 | surface with sealing ring | 10 | 0,038 |
| K- 07 30 30 74 | 3 | for hose outer-Ø10 mm | outer thread R 3/8 | Teflon coated | 10 | 0,029 |
| K- 07 30 30 78 | 3 | for hose outer-Ø10 mm | outer thread G 3/8 | surface with sealing ring | 10 | 0,029 |
| K- 07 30 30 75 | 3 | for hose outer-Ø12 mm | outer thread R 3/8 | Teflon coated | 10 | 0,041 |
| K- 07 30 30 79 | 4 | for hose outer-Ø10 mm | outer thread R 1/2 | Teflon coated | 10 | 0,062 |
| K- 07 30 30 82 | 4 | for hose outer-Ø10 mm | outer thread G 1/2 | surface with sealing ring | 10 | 0,062 |
| K- 07 30 30 80 | 4 | for hose outer-Ø12 mm | outer thread R 1/2 | Teflon coated | 10 | 0,064 |
| K- 07 30 30 83 | 4 | for hose outer-Ø12 mm | outer thread G 1/2 | surface with sealing ring | 10 | 0,064 |
| K- 07 30 30 81 | 4 | for hose outer-Ø16 mm | outer thread R 1/2 | Teflon coated | 10 | 0,068 |
| K- 07 30 30 84 | 4 | for hose outer-Ø16 mm | outer thread G 1/2 | surface with sealing ring | 10 | 0,068 |