

Vlastnosti

| | |
|--------------------------|-----------------------------|
| Prípojka 1 | Vonkajší závit BSP, valcový |
| Konštrukcia | Dutá skrutka |
| Materiál | Oceľ |
| Povrchová ochrana | galvanický povlak |



Výrobok

| Označenie | G1 | Ø d2 (mm) | L2 (mm) | m (mm) | S1 |
|-----------------|------------|--------------|------------|-----------|----|
| HS R 1/8 | G 1/8" -28 | 9,9 | 19,0 | 5 | 14 |
| HS R 1/4 | G 1/4" -19 | 13,1 | 25,5 | 5 | 17 |
| HS R 3/8 | G 3/8" -19 | 16,6 | 31,0 | 7 | 22 |
| HS R 1/2 | G 1/2" -14 | 20,9 | 40,0 | 8 | 27 |
| HS R 5/8 | G 5/8" -14 | 22,9 | 47,0 | 9 | 32 |
| HS R 3/4 | G 3/4" -14 | 26,4 | 47,0 | - | 32 |
| HS R 1 | G 1" -11 | 33,2 | 58,0 | 10 | 41 |

SW, S1, S2 = Šírka kľúča

Varianty produktu

HS R VA Dutá skrutka, Ušľachtilá oceľ