

# 2 OK VA

Svorka s 2 okami

## Vlastnosti

**Oblasť použitia** Upevňovanie hadíc v nízkotlakovej oblasti

**Materiál** Ušľachtilá oceľ



## Výrobok

| Označenie       | Rozsah upínania (mm) | Šírka pásu (mm) |
|-----------------|----------------------|-----------------|
| 2 OK 3-5 VA     | 3,4 - 5,0            | 5,0             |
| 2 OK 3.1-4.1 VA | 3,1 - 4,1            | 3,5             |
| 2 OK 3.5-4.5 VA | 3,5 - 4,5            | 3,5             |
| 2 OK 5-7 VA     | 5,0 - 7,0            | 6,0             |
| 2 OK 7-9 VA     | 7,0 - 9,0            | 6,0             |
| 2 OK 8-11 VA    | 8,0 - 11,0           | 7,0             |
| 2 OK 9-11 VA    | 9,0 - 11,0           | 6,5             |
| 2 OK 11-13 VA   | 11,0 - 13,0          | 6,5             |
| 2 OK 13-15 VA   | 13,0 - 15,0          | 7,0             |
| 2 OK 15-17 VA   | 15,0 - 17,0          | 7,5             |
| 2 OK 15-18 VA   | 15,0 - 18,0          | 7,5             |
| 2 OK 17-20 VA   | 17,0 - 20,0          | 7,5             |
| 2 OK 18-21 VA   | 18,0 - 21,0          | 8,0             |
| 2 OK 19-22 VA   | 18,1 - 22,0          | 9,0             |
| 2 OK 20-23 VA   | 20,0 - 23,0          | 8,0             |
| 2 OK 22-25 VA   | 22,0 - 25,0          | 8,5             |
| 2 OK 23-27 VA   | 23,0 - 27,0          | 8,5             |
| 2 OK 25-28 VA   | 25,0 - 28,0          | 9,0             |
| 2 OK 27-31 VA   | 26,3 - 31,0          | 10,0            |
| 2 OK 28-31 VA   | 28,0 - 31,0          | 9,0             |
| 2 OK 31-34 VA   | 31,0 - 34,0          | 9,5             |
| 2 OK 34-37 VA   | 34,0 - 37,0          | 9,5             |
| 2 OK 37-40 VA   | 37,0 - 40,0          | 10,0            |
| 2 OK 40-43 VA   | 40,0 - 43,0          | 10,0            |
| 2 OK 43-46 VA   | 43,0 - 46,0          | 10,0            |

## Varianty produktu

**2 OK** Svorka s 2 okami, galvanický povlak

**2 OK VC** Svorka s 2 okami, chrómovo lesklo pozinkované