

Vlastnosti

Konštrukcia	bezskrútkové hadicové objímky
Materiál	Korózievzdorná chrómniklová oceľ



Popis

Hadicová objímka CLIC je spoľahlivým spojovacím prostriedkom pre systémy hrdiel hadíc.

Výrobok

Označenie	Rozsah upínania (mm)	Šírka pásu (mm)
CLIC 11.5-12.5	11,5 - 12,5	7,0
CLIC 12-13	12,0 - 13,0	7,0
CLIC 13-14	12,5 - 14,0	8,0
CLIC 14-15	13,5 - 15,0	8,0
CLIC 15-16	14,5 - 16,0	8,0
CLIC 16-17	15,5 - 17,0	8,0
CLIC 17-18	16,5 - 18,0	8,0
CLIC 18-19	17,5 - 19,0	8,0
CLIC 19-20	18,5 - 20,0	8,0
CLIC 20-21	19,5 - 21,0	8,0
CLIC 20.5-21.5	20,5 - 22,0	8,0
CLIC 21.5-23	21,5 - 23,0	8,0
CLIC 22.5-24	22,5 - 24,0	8,0
CLIC 23.5-25	23,5 - 25,0	8,0
CLIC 25.5-27	25,5 - 27,0	8,0
CLIC 26.5-28	26,5 - 28,0	8,0

Príslušenstvo

CLIC ZANGE Kliešte pre objímku CLIC