

### Vlastnosti

**Konštrukcia** bezskrutkové hadicové objímky

**Materiál** Korózievzdorná chrómniková oceľ



### Popis

Hadicová objímka CLIC je spoľahlivým spojovacím prostriedkom pre systémy hrdiel hadíc.

### Výrobok

| Označenie      | Rozsah upínania (mm) | Šírka pásu (mm) |
|----------------|----------------------|-----------------|
| CLIC 11.5-12.5 | 11,5 - 12,5          | 7,0             |
| CLIC 12-13     | 12,0 - 13,0          | 7,0             |
| CLIC 13-14     | 12,5 - 14,0          | 8,0             |
| CLIC 14-15     | 13,5 - 15,0          | 8,0             |
| CLIC 15-16     | 14,5 - 16,0          | 8,0             |
| CLIC 16-17     | 15,5 - 17,0          | 8,0             |
| CLIC 17-18     | 16,5 - 18,0          | 8,0             |
| CLIC 18-19     | 17,5 - 19,0          | 8,0             |
| CLIC 19-20     | 18,5 - 20,0          | 8,0             |
| CLIC 20-21     | 19,5 - 21,0          | 8,0             |
| CLIC 20.5-21.5 | 20,5 - 22,0          | 8,0             |
| CLIC 21.5-23   | 21,5 - 23,0          | 8,0             |
| CLIC 22.5-24   | 22,5 - 24,0          | 8,0             |
| CLIC 23.5-25   | 23,5 - 25,0          | 8,0             |
| CLIC 25.5-27   | 25,5 - 27,0          | 8,0             |
| CLIC 26.5-28   | 26,5 - 28,0          | 8,0             |

### Príslušenstvo

**CLIC ZANGE** Kliešte pre objímku CLIC