

# HK CFB

Dno závesného valca s vtokom oleja

**HANSA FLEX**

## Vlastnosti

**Materiál** Oceľ S355J0 (Fe510C)



## Výrobok

| Označenie        | Ø AL<br>(mm) | Ø F<br>(mm) | Ø T<br>(mm) | C<br>(mm) | G      | V<br>(mm) | I<br>(mm) | S<br>(mm) | Z<br>(mm) | Hmotnosť<br>(kg) |
|------------------|--------------|-------------|-------------|-----------|--------|-----------|-----------|-----------|-----------|------------------|
| HK CFB 040 050 4 | 40           | 16,20       | 50          | 24,8      | G 1/4" | 19,0      | 39,0      | 2,00      | 46        | 0,56             |
| HK CFB 050 060 6 | 50           | 20,25       | 60          | 24,8      | G 3/8" | 31,0      | 56,0      | 2,00      | 51        | 0,84             |
| HK CFB 060 070 6 | 60           | 25,25       | 70          | 24,8      | G 3/8" | 33,0      | 63,0      | 2,00      | 57        | 1,15             |
| HK CFB 061 071 6 | 60           | 25,25       | 70          | 25,0      | G 3/8" | 29,5      | 48,0      | 2,00      | 47        | 0,81             |
| HK CFB 070 080 6 | 70           | 25,25       | 80          | 39,5      | G 3/8" | 42,0      | 82,0      | 2,00      | 65        | 2,70             |