

K-PVDF-SCHLAUCH NATUR

PVDF tubing nature

HANSA FLEX

Vlastnosti

Použitie resistant to a variety of chemicals


Vnútoraná vrstva PVDF

Vonkajšia vrstva PVDF

Farba Natural

Teplota min. -40 °C

Teplota max. 150 °C



Dodatočné informácie

- very good temperature resistance
- extremely high pressure resistance
- sterilisable
- non-combustible (to UL 94 V-O)
- very good UV resistance
- very low gas permeability
- excellent mechanical properties

Výrobok

| Označenie | Vnútorný Ø (mm) | Vonkajší Ø (mm) | Hrúbky steny (mm) | Polomer ohybu min. (mm) | Dĺžka kladky (m) |
|----------------|--------------------|--------------------|----------------------|----------------------------|---------------------|
| K- 07 10 13 16 | 2,0 | 4,0 | 1,0 | 60 | 100 |
| K- 07 10 13 17 | 4,0 | 6,0 | 1,0 | 75 | 100 |
| K- 07 10 13 18 | 6,0 | 8,0 | 1,0 | 85 | 100 |
| K- 07 10 13 19 | 8,0 | 10,0 | 1,0 | 100 | 100 |
| K- 07 10 13 20 | 10,0 | 12,0 | 1,0 | 125 | 100 |