

K-PUR-BREMSSPIRALE

PUR brake coil with connection

HANSA FLEX

Vlastnosti

Prípojka 1 + 2	metrický vonkajší závit valcový
Norma	tested in accordance with DIN 74323 DIN 74324 ISO 7268-2 ISO 7375-2 DIN 73378 DIN 74310-2
Certifikát	German Technical Surveyance Association (TÜV)-type approved (Certificate R 9910199)
Teplota min.	-40 °C
Teplota max.	90 °C
Materiál	PUR



Dodatočné informácie

- will not break at fittings
- excellent antikink characteristics – kinking leaves no defects
- longer operation length
- highly resistant to tearing off at fittings
- excellent springback characteristics
- unplasticized so no embrittlement
- resistant to oil and grease
- resistant to UV and ozon
- service life many times longer than conventional coil tubing

Výrobok

Označenie	G1 + G2	Vnútorňý Ø (mm)	Vonkajší Ø (mm)	Hrúbky steny (mm)	Dĺžka (m)	Farba
K- 07 10 13 21	M 16 x 1,5	8,0	12,0	2,0	4,50	čierna
K- 07 10 13 22	M 16 x 1,5	8,0	12,0	2,0	4,50	žltá
K- 07 10 13 23	M 16 x 1,5	8,0	12,0	2,0	4,50	červená
K- 07 10 13 24	M 16 x 1,5	8,0	12,0	2,0	5,50	čierna
K- 07 10 13 25	M 16 x 1,5	8,0	12,0	2,0	5,50	žltá
K- 07 10 13 26	M 16 x 1,5	8,0	12,0	2,0	5,50	červená