# K-MANO 1

Pressure gauges (CrNi steel type / safety housing)

HANSA FLEX

## Vlastnosti

| | |
|---|---|
| **Typ** | 232.30 |
| **Vyhotovenie** | Bourdon-tube pressure gauge, CrNi steel type, with solid baffle wall and blow-out (safety housing) |
| **Použitie** | For gaseous or liquid, corrosive and crystallising mediawhich do not have high viscosity, also in corrosive atmosphere |
| **Akostná trieda** | 1,6 (Ø 63 mm), 1,0 (Ø 100 mm) |
| **Teplota média** | max. +200 °C |
| **Teplota okolia** | -40 °C to +60 °C |
| **Kryt** | CrNi steel |
| **Priehľadný kryt stupnice** | Laminated safety glass Ø 63 = Polycarbonate |




## Poznámka

Ďalšie údaje na vyžiadanie.

## Popis

Safety version with more fracture-resistant separating wall

## Výrobok

| Označenie | Rozsah merania | Ø (mm) | Prípojka |
|---|---|---|---|
| **K- 07 20 07 15** | -1 / 0.0 bar | 63,0 | G 1/4" |
| **K- 07 20 07 16** | 0 - 1.6 bar | 63,0 | G 1/4" |
| **K- 07 20 07 17** | 0 - 2.5 bar | 63,0 | G 1/4" |
| **K- 07 20 07 18** | 0 - 4.0 bar | 63,0 | G 1/4" |
| **K- 07 20 07 19** | 0 - 6.0 bar | 63,0 | G 1/4" |
| **K- 07 20 07 20** | 0 - 10.0 bar | 63,0 | G 1/4" |
| **K- 07 20 07 21** | 0 - 16.0 bar | 63,0 | G 1/4" |
| **K- 07 20 07 22** | 0 - 25.0 bar | 63,0 | G 1/4" |
| **K- 07 20 07 23** | 0 - 40.0 bar | 63,0 | G 1/4" |
| **K- 07 20 07 24** | 0 - 60.0 bar | 63,0 | G 1/4" |
| **K- 07 20 07 25** | 0 - 100.0 bar | 63,0 | G 1/4" |
| **K- 07 20 01 97** | 0 - 1.0 bar | 100,0 | G 1/2" |
| **K- 07 20 01 98** | 0 - 1.6 bar | 100,0 | G 1/2" |
| **K- 07 20 01 99** | 0 - 2.5 bar | 100,0 | G 1/2" |
| **K- 07 20 02 00** | 0 - 4.0 bar | 100,0 | G 1/2" |
| **K- 07 20 02 01** | 0 - 6.0 bar | 100,0 | G 1/2" |
| **K- 07 20 02 02** | 0 - 10.0 bar | 100,0 | G 1/2" |
| **K- 07 20 02 03** | 0 - 16.0 bar | 100,0 | G 1/2" |
| **K- 07 20 02 04** | 0 - 25.0 bar | 100,0 | G 1/2" |
| **K- 07 20 02 05** | 0 - 40.0 bar | 100,0 | G 1/2" |
| **K- 07 20 02 06** | 0 - 60.0 bar | 100,0 | G 1/2" |
| **K- 07 20 02 07** | 0 - 100.0 bar | 100,0 | G 1/2" |
| **K- 07 20 02 08** | 0 - 160.0 bar | 100,0 | G 1/2" |
| **K- 07 20 02 09** | 0 - 250.0 bar | 100,0 | G 1/2" |
| **K- 07 20 02 10** | 0 - 400.0 bar | 100,0 | G 1/2" |