

K-PRMM ROB U

Robust diaphragm pressure gauges, connection radial on bottom

HANSA FLEX

Vlastnosti

Typ	422.12 (robust), 432.50 (chemical)
Vyhotovenie	Diaphragm pressure gauge in robust design or for chemical applications
Použitie	at chemical applications in aggressive environments for gaseous or liquid media,
Akostná trieda	1,6
Teplota média	max. +100 °C
Teplota okolia	-20 °C až +60 °C
Ø meracia príruha	100 mm
kryt, krúžok	Grey cast iron / CrNi steel, black (robust type), CrNi steel (type for chemical applications)
Merací člen	CrNi steel
Priehľadný kryt stupnice	Flat instrument glass (robust type), Laminated safety glass (type for chemical applications)
ukazovateľ	Copper alloy (robust type), CrNi steel (type for chemical applications)



Poznámka

Ďalšie údaje na vyžiadanie.

Výrobok

Označenie	Rozsah merania	Ø (mm)	Prípojka
K- 07 20 10 99	-1 / +1.5 bar	100,0	G 1/2"
K- 07 20 11 00	0 - 1.0 bar	100,0	G 1/2"
K- 07 20 11 01	0 - 1.6 bar	100,0	G 1/2"
K- 07 20 11 02	0 - 2.5 bar	100,0	G 1/2"
K- 07 20 11 03	0 - 4.0 bar	100,0	G 1/2"
K- 07 20 11 04	0 - 6.0 bar	100,0	G 1/2"
K- 07 20 11 05	0 - 10.0 bar	100,0	G 1/2"
K- 07 20 11 06	0 - 16.0 bar	100,0	G 1/2"
K- 07 20 11 07	0 - 25.0 bar	100,0	G 1/2"