

# K-PRMM CHEMIE U

Diaphragm pressure gauges for chemical applications, connection radial on bottom

**HANSA FLEX**

## Vlastnosti

<b>Typ</b>	422.12 (robust), 432.50 (chemical)
<b>Vyhotovenie</b>	Diaphragm pressure gauge in robust design or for chemical applications
<b>Použitie</b>	at chemical applications in aggressive environments for gaseous or liquid media,
<b>Akostná trieda</b>	1,6
<b>Teplota média</b>	max. +100 °C
<b>Teplota okolia</b>	-20 °C až +60 °C
<b>Ø meracia príruha</b>	100 mm
<b>kryt, krúžok</b>	Grey cast iron / CrNi steel, black (robust type), CrNi steel (type for chemical applications)
<b>Merací člen</b>	CrNi steel
<b>Priehľadný kryt stupnice</b>	Flat instrument glass (robust type), Laminated safety glass (type for chemical applications)
<b>ukazovateľ</b>	Copper alloy (robust type), CrNi steel (type for chemical applications)



## Poznámka

Ďalšie údaje na vyžiadanie.

## Výrobok

Označenie	Rozsah merania	Ø (mm)	Prípojka
K- 07 20 10 25	0 - 6.0 bar	100,0	G 1/2"
K- 07 20 10 26	0 - 10.0 bar	100,0	G 1/2"