


# K-MANO ABSPH MUF MUF

Pressure gauge stopcocks, female - female

**HANSA FLEX**

## Vlastnosti

|                         |   |
|-------------------------|---|
| <b>Použitie</b>         | For all pressure gauges with a flat gasket acc. to DIN 16258                                    |
| <b>Rozsah tlaku</b>     | Max. 16 bar, depending on the variant Pressure gauge valves should be used for higher pressures |
| <b>Teplota</b>          | Max. +50 °C   |
| <b>Kryt</b>             | Brass with a bare metal surface or stainless steel 1.4571                                       |
| <b>držadlo</b>          | Plastic   |
| <b>Skúšobná príruka</b> | -   |



## Poznámka

K-07201090, K-07201091 in acc. with DIN 16261-A, K-07201096, K-07201097 in acc. with DIN 16261-B <br>K-07201128, K-07201129 in acc. with DIN 16262-A, K-07201127 in acc. with DIN 16262-B

Ďalšie údaje na vyžiadanie.

## Popis

It is useful to install a stopcock as a shut-off element between the pressure gauge and the pipe. When the lever is set to the »blow out« position, the medium is discharged into the atmosphere. Stopcocks with a test port allow pressure gauges to be simultaneously connected to the pipe.

## Dodatočné informácie

Further measuring ranges on request

Version for panel mounting available on request. Version with max. pointer available on request

## Výrobok

| Označenie      | Závit | PN (bar) | SW (mm) | Materiál        |
|----------------|-------|----------|---------|-----------------|
| K- 07 20 10 88 | G 1/4 | 6        | 17      | Mosadz          |
| K- 07 20 10 89 | G 3/8 | 16       | 22      | Mosadz          |
| K- 07 20 10 91 | G 1/2 | 25       | 27      | Mosadz          |
| K- 07 20 10 90 | G 1/2 | 25       | 27      | Stainless steel |
| K- 07 20 10 93 | G 1/2 | 25       | 27      | Mosadz          |
| K- 07 20 10 92 | G 1/2 | 25       | 27      | Mosadz          |