
# K-MANO ABSPH MUF DREH MUF

Pressure gauge stopcocks, female - loose (rotatable) female

## Vlastnosti

| | |
|---|---|
| **Použitie** | For all pressure gauges with a flat gasket acc. to DIN 16258 |
| **Rozsah tlaku** | Max. 16 bar, depending on the variantPressure gauge valves should be used for higher pressures |
| **Teplota** | Max. +50 °C |
| **Kryt** | Brass with a bare metal surface or stainless steel 1.4571 |
| **držadlo** | Plastic |
| **Skúšobná príruba** | - |



## Poznámka

K-07201090, K-07201091 in acc. with DIN 16261-A, K-07201096, K-07201097 in acc. with DIN 16261-B <br>K-07201128, K-07201129 in acc. with DIN 16262-A, K-07201127 in acc. with DIN 16262-B
Ďalšie údaje na vyžiadanie.

## Popis

It is useful to install a stopcock as a shut-off element between the pressure gauge and the pipe. When the lever is set to the »blow out« position, the medium is discharged into the atmosphere. Stopcocks with a test port allow pressure gauges to be simultaneously connected to the pipe.

## Dodatočné informácie

Further measuring ranges on request
Version for panel mounting available on request. Version with max. pointer available on request

## Výrobok

| Označenie | Závit | PN (bar) | SW (mm) | Materiál |
|---|---|---|---|---|
| **K- 07 20 10 86** | G 1/2 | 25 | 27 | Mosadz |
| **K- 07 20 10 87** | G 1/2 | 25 | 27 | Mosadz |