K-MANO ABSPH ZAPF SPAN MUF

Pressure gauge stopcocks, male - female/female

Vlastnosti

Použitie	For all pressure gauges with a flat gasket acc. to DIN 16258
Rozsah tlaku	Max. 16 bar, depending on the variantPressure gauge valves should be used for higher pressures
Teplota	Max. +50 °C
Kryt	Brass with a bare metal surface or stainless steel 1.4571
držadlo	Plastic
Skúšobná príruba	-



Poznámka

K-07201090, K-07201091 in acc. with DIN 16261-A, K-07201096, K-07201097 in acc. with DIN 16261-B
K-07201128, K-07201129 in acc. with DIN 16262-A, K-07201127 in acc. with DIN 16262-B
Ďalšie údaje na vyžiadanie.

Popis

It is useful to install a stopcock as a shut-off element between the pressure gauge and the pipe. When the lever is set to the »blow out« position, the medium is discharged into the atmosphere. Stopcocks with a test port allow pressure gauges to be simultaneously connected to the pipe.

Dodatočné informácie

Further measuring ranges on request
Version for panel mounting available on request. Version with max. pointer available on request

Výrobok

Označenie	Závit	PN (bar)	SW (mm)	Materiál
K- 07 20 11 27	G 1/4	6	17	Mosadz
K- 07 20 11 29	G 1/2	25	27	Mosadz
K- 07 20 11 28	G 1/2	25	27	Stainless steel
K- 07 20 11 31	G 1/2	25	27	Mosadz
K- 07 20 11 30	G 1/2	25	27	Stainless steel
K- 07 20 11 32	G 1/2	25	27	Mosadz