

# K-MANO ABSPV ZAPF SPAN MUF PRUEFFL

Pressure gauge valves, male - female/female, with test flange 60 x 25 x 10

**HANSA FLEX**

## Vlastnosti

|                                   |  |
|-----------------------------------|--|
| Prevádzkový tlak                  | max. 250 bar brass, max. 400 bar steel/<br>stainless steel         |
| Teplota                           | Max. +120 °C with brass/steel;<br>Max. +200 °C for stainless steel |
| Materiál všetkých súčastí         | Stainless steel  |
| Tesniaci materiál                 | PTFE   |
| Kryt                              | Brass, black-finished steel or stainless<br>steel 1.4571           |
| ručné koleso                      | Plastic  |
| prevlečná matica napínacia matica | Steel  |
| vreteno ventilu, ventilový kužel  | Stainless steel  |



## Poznámka

Ďalšie údaje na vyžiadanie.

## Popis

They are used as shut-off or reducing elements for pressure gauges when measuring liquids, gases or steam.

## Výrobok

| Označenie      | Závit | PN (bar) | SW<br>(mm) | Materiál        |
|----------------|-------|----------|------------|-----------------|
| K- 07 20 11 34 | G 1/2 | 250      | 27         | Mosadz          |
| K- 07 20 11 33 | G 1/2 | 400      | 27         | Stainless steel |