

K-RMM HKR STAHL

Standard pressure gauges with 3-hole bezel, chrome-plated steel, dual scale in bar/psi and clamp fixing, connection on rear

HANSA FLEX

Vlastnosti

Typ	111.12
Vyhotovenie	Bourdon-tube pressure gauge, standard design, mounting ring Chromium plated sheet steel Steel chrome plated or black or with triangular bezel
Použitie	gaseous or liquid media which do not corrode copper alloy, do not have high viscosity and do not crystallise
Akostná trieda	2,5
Teplota média	max. +60 °C
Teplota okolia	-20 °C až +60 °C
Kryt	Sheet steel
Materiál meracie člena a ukazovateľa	Zliatina medi
Priehľadný kryt stupnice	Transparent plastic



Poznámka

Ďalšie údaje na vyžiadanie.

Výrobok

Označenie	Rozsah merania	Ø (mm)	Prípojka
K- 07 20 04 04	-1 / 0.0 bar	40,0	G 1/8
K- 07 20 04 05	0 - 1.0 bar	40,0	G 1/8
K- 07 20 04 06	0 - 1.6 bar	40,0	G 1/8
K- 07 20 04 07	0 - 2.5 bar	40,0	G 1/8
K- 07 20 04 08	0 - 4.0 bar	40,0	G 1/8
K- 07 20 04 09	0 - 6.0 bar	40,0	G 1/8
K- 07 20 04 10	0 - 10.0 bar	40,0	G 1/8
K- 07 20 04 11	0 - 16.0 bar	40,0	G 1/8
K- 07 20 04 12	0 - 25.0 bar	40,0	G 1/8