

# K-RMM U KUNSTSTOFF MZ

Standard pressure gauges, connection radial on bottom

**HANSA FLEX**

## Vlastnosti

Typ	111.10 (radial connector on bottom)
Vyhotovenie	Bourdon-tube pressure gauge in standard design
Použitie	gaseous or liquid media which do not corrode copper alloy, do not have high viscosity and do not crystallise
Akostná trieda	1.6 (Art No. K-07200303, K-07403298 - K-07201188: 2.5)
Ručička označenia	(for Ø 160 mm - red pointer on the scale) red pointer to the window. For measuring ranges 0...0,6 bar bis 0...60 bar
Teplota média	max. +60 °C
Teplota okolia	-20 °C až +60 °C
Kryt	Plastic
Materiál meracie člena a ukazovateľa	Zliatina medi
Priehľadný kryt stupnice	Transparent plastic



## Poznámka

Ďalšie údaje na vyžiadanie.

## Výrobok

Označenie	Rozsah merania	Ø (mm)	Prípojka
K- 07 20 03 03	-1200 / 0.0 mbar	100,0	G 1/2"
K- 07 20 03 04	-1 / 0.0 bar	100,0	G 1/2"
K- 07 20 03 05	-1 / +0.6 bar	100,0	G 1/2"
K- 07 20 03 06	-1 / +1.5 bar	100,0	G 1/2"
K- 07 20 03 07	-1 / +3.0 bar	100,0	G 1/2"
K- 07 20 03 08	-1 / +5.0 bar	100,0	G 1/2"
K- 07 20 03 09	-1 / +9.0 bar	100,0	G 1/2"
K- 07 20 02 84	0 - 0.6 bar	100,0	G 1/2"
K- 07 20 02 85	0 - 1.0 bar	100,0	G 1/2"
K- 07 20 02 86	0 - 1.6 bar	100,0	G 1/2"
K- 07 20 02 87	0 - 2.5 bar	100,0	G 1/2"
K- 07 20 02 88	0 - 4.0 bar	100,0	G 1/2"
K- 07 20 02 89	0 - 6.0 bar	100,0	G 1/2"
K- 07 20 02 90	0 - 10.0 bar	100,0	G 1/2"
K- 07 20 02 91	0 - 16.0 bar	100,0	G 1/2"
K- 07 20 02 92	0 - 25.0 bar	100,0	G 1/2"
K- 07 20 02 93	0 - 40.0 bar	100,0	G 1/2"
K- 07 20 11 86	0 - 60.0 bar	100,0	G 1/2"
K- 07 20 11 87	0 - 100.0 bar	100,0	G 1/2"
K- 07 20 11 88	0 - 160.0 bar	100,0	G 1/2"