# K-TR PA 12 ROLLE

Plastic pipes on coils, polyamide PA 12

## Vlastnosti

| | |
|---|---|
| **Prevádzková teplota** | -60 °C to +100 °C (PA 12) |
| **Vlastnosti** | Resistant to corrosion, vibration, impact, ageing, high pressures and heat |
| **Materiál** | Polyamid PA 12, hard (according to DIN 73378) |



## Poznámka

Operating pressure with 2.5 x overpressure safety!
Ďalšie údaje na vyžiadanie.

## Popis

Push-in fittings - aluminium pipes - plastic pipes - take-off points. The flexible, maintenance-free compressed air installation system from compressor to take-off point. For Ø 12 mm to Ø 32 mm pipe systems and for Ø 4 mm to Ø 12 mm pneumatic applications

## Výrobok

| Označenie | vnútorný Ø hadice (mm) | vonkajší Ø hadice (mm) | max. prevádzkový tlak pri 20°C (bar) | Dĺžka kladky (m) |
|---|---|---|---|---|
| **K- 07 10 04 77** | 9,0 | 12,0 | 19 | 25 |
| **K- 07 10 04 79** | 12,0 | 15,0 | 15 | 25 |
| **K- 07 10 04 81** | 14,0 | 18,0 | 16 | 25 |
| **K- 07 10 04 83** | 18,0 | 22,0 | 14 | 25 |
| **K- 07 10 04 76** | 9,0 | 12,0 | 19 | 100 |
| **K- 07 10 04 78** | 12,0 | 15,0 | 15 | 100 |
| **K- 07 10 04 80** | 14,0 | 18,0 | 16 | 100 |
| **K- 07 10 04 82** | 18,0 | 22,0 | 14 | 100 |
| **K- 07 10 04 84** | 23,0 | 28,0 | 14 | 50 |

*Napriek čo najstarostlivejšej kontrole nemôžeme vylúčiť chyby a nepreberáme žiadnu záruku za zahrnuté údaje.*