

K-TR PA 12

Plastic pipes made of polyamide PA 12 (20 pcs.)

HANSA FLEX

Vlastnosti

Prevádzková teplota	-60 °C to +100 °C (PA 12)
Vlastnosti	Resistant to corrosion, vibration, impact, ageing, high pressures and heat
Dĺžka rúrky	3 m
Jednotka balenia	20 lengths (O.D. 28 mm in packs of 10 lengths), only sold in complete packaging units!
Materiál	Polyamid PA 12, hard (according to DIN 73378)



Poznámka

Operating pressure with 2.5 x overpressure safety!

Ďalšie údaje na vyžiadanie.

Popis

Push-in fittings - aluminium pipes - plastic pipes - take-off points. The flexible, maintenance-free compressed air installation system from compressor to take-off point. For Ø 12 mm to Ø 32 mm pipe systems and for Ø 4 mm to Ø 12 mm pneumatic applications

Výrobok

Označenie	Rúrka, vonkajší Ø (mm)	Vnútorný Ø rúrky (mm)	max. prevádzkový tlak pri 20°C (bar)	Farba
K- 07 10 04 56	12	9	38	modrá
K- 07 10 04 58	12	9	38	čierna
K- 07 10 04 60	15	12	25	modrá
K- 07 10 04 62	15	12	25	čierna
K- 07 10 04 64	18	14	28	modrá
K- 07 10 04 66	18	14	28	čierna
K- 07 10 04 68	22	18	22	modrá
K- 07 10 04 70	22	18	22	čierna
K- 07 10 04 72	28	23	20	modrá
K- 07 10 04 74	28	23	20	čierna