K-SPIR SCHL

Spiral hose, without fittings

Vlastnosti

Použitie	Air, gases, oils, greases, fuels, organic and inorganic substances
Prevádzková teplota	-40 °C to +100 °C



Poznámka

Ďalšie údaje na vyžiadanie.

Popis

These hoses allow gaseous and liquid media to flow safely and efficiently (Air, gases, oils, greases, fuels, organic and inorganic substances). Thanks to their small coil diameter, they are compact, easy to handle and lightweight. Very good recoil force owing to the use of nylon 12 (PA).

Výrobok

Označenie	vnútorný Ø hadice (mm)	vonkajší Ø hadice (mm)	vonkajší Ø špirály (mm)	Vinutia	Max. working pressure resistance at 23° C (bar)	max. pracovná dĺžka (m)
K- 07 10 07 51	3,1	4,7	38	144	22	10,0
K- 07 10 07 52	4,8	6,3	75	140	16	22,5
K- 07 10 07 53	6,3	7,9	75	135	13	22,5
K- 07 10 07 49	7,9	9,5	115	90	12	22,5
K- 07 10 07 50	9,5	11,8	140	70	11	22,5

Príslušenstvo

K-DREHBARE VERSCHR KNICK	Swivel adapters with kink protector
K-STARRE VERSCHRAUBUNG	Rigid adapters with kink protector

Napriek čo najstarostlivejšej kontrole nemôžeme vylúčiť chyby a nepreberáme žiadnu záruku za zahrnuté údaje.