

K-VSEH 3-KRAFT

Receptacle combinations »3-Kraft«

HANSA FLEX

Vlastnosti

Kryt	Amaplast with hinged cover
Integrovaný v kryte	Hanging eyelets, wall mounting fixing and standing feet
Vyhotovenie	Pre-wired
Prívody vodičov	Top: 1 x M 32, 1 x M 25, 2 x M 20; Side: 1 x M 25; One opening at the top for pneumatic connection or grabrails (all introductions to break)
Krytie	IP 44



Poznámka

Ďalšie údaje na vyžiadanie.

Popis

Receptacle combination with low power, high power or combined connections. Equipped with a pneumatic connection (DN 7.2 coupling with 9 mm stem).

Výrobok

Označenie	Osadenie	Farba
K- 07 10 03 50	3 Schuko socket 16 A 2p + E 230 V	žltá
K- 07 10 03 49	2 Schuko socket 16 A 2p + E 230 V, 1 CEEform socket 16 A 5p 400 V	striebro

Príslušenstvo

K-VT 2 KUPPL 7,2 STECKNIP MS	Distributors with 2 quick disconnect couplings DN 7.2, brass with push in plug DN 7.2 - DN 7.8
K-ZUBEH VSEH 3 KRAFT AIRKRAFT	Accessories for receptacle combinations »3-Kraft« and »airkraft«