

K-VERSCHLUSSNIPPEL IG MS

Self-sealing plugs, brass

HANSA FLEX

Vlastnosti

| | |
|--------------------------------|---|
| Prevádzkový tlak | See table. All values referred to a medium temperature of 50 °C (static working pressure) |
| Prietok vzduch | 440 l/min (G 1/8), 840 l/min (G 1/4), 1.280 l/min (G 3/8), 1.950 l/min (G 1/2), 4.500 l/min (G 3/4) (at 6 bar and $\Delta p = 0,5$ bar) |
| Teplota média | -20 °C to +100 °C |
| kryt, puzdro, ventil | Brass |
| pružina, rozperný krúžok, gule | stain less steel |
| Tesniaci materiál | NBR |



Poznámka

Ďalšie údaje na vyžiadanie.

Popis

Hydraulic couplings, both sides sealing, for liquid media acc. to ISO 7241, B Series.

Výrobok

| Označenie | Prípojka | MS | Prevádzkový tlak (bar) | Dĺžka (mm) | SW (mm) |
|----------------|--------------|------|------------------------|------------|---------|
| K- 07 40 10 15 | G 1/8 female | 4,3 | 250,0 | 29,5 | 14 |
| K- 07 40 10 16 | G 1/4 female | 6,3 | 200,0 | 35,3 | 19 |
| K- 07 40 10 17 | G 3/8 female | 7,5 | 200,0 | 39,0 | 22 |
| K- 07 40 10 18 | G 1/2 female | 11,0 | 150,0 | 48,0 | 27 |
| K- 07 40 10 19 | G 3/4 female | 13,0 | 100,0 | 60,0 | 36 |