


K-VERSCHLUSSNIPPEL IG POM

Self-sealing plugs, POM

HANSA FLEX

Vlastnosti

Prevádzkový tlak	See table. All values referred to a medium temperature of 50 °C (static working pressure)
Prietok vzduch	440 l/min (G 1/8), 840 l/min (G 1/4), 1.280 l/min (G 3/8), 1.950 l/min (G 1/2), 4.500 l/min (G 3/4) (at 6 bar and $\Delta p = 0,5$ bar)
Teplota média	-20 °C to +90 °C
kryt, puzdro	POM (Delrin), white
Ventil	Stainless steel 1.4305
pružina, rozperný krúžok, gule	stain less steel
Tesniaci materiál	NBR



Poznámka

Ďalšie údaje na vyžiadanie.

Popis

Hydraulic couplings, both sides sealing, for liquid media acc. to ISO 7241, B Series.

Výrobok

Označenie	Prípojka	Prevádzkový tlak (bar)	Dĺžka (mm)	MS	SW (mm)
K- 07 40 39 58	G 1/8 female	15,0	29,5	4,3	14
K- 07 40 39 59	G 1/4 female	15,0	35,3	6,0	19
K- 07 40 39 60	G 3/8 female	15,0	39,0	7,5	22
K- 07 40 39 61	G 1/2 female	10,0	48,0	11,0	27
K- 07 40 39 62	G 3/4 female	10,0	60,0	13,0	36