


# K-VERSCHLUSSNIPPEL IG POM

Self-sealing plugs, POM

**HANSA FLEX**

## Vlastnosti

Prevádzkový tlak	See table. All values referred to a medium temperature of 50 °C (static working pressure)
Prietok vzduch	440 l/min (G 1/8), 840 l/min (G 1/4), 1.280 l/min (G 3/8), 1.950 l/min (G 1/2), 4.500 l/min (G 3/4) (at 6 bar and $\Delta p = 0,5$ bar)
Teplota média	-20 °C to +90 °C
kryt, puzdro	POM (Delrin), white
Ventil	Stainless steel 1.4305
pružina, rozperný krúžok, gule	stain less steel
Tesniaci materiál	NBR



## Poznámka

Ďalšie údaje na vyžiadanie.

## Popis

Hydraulic couplings, both sides sealing, for liquid media acc. to ISO 7241, B Series.

## Výrobok

Označenie	Prípojka	Prevádzkový tlak (bar)	Dĺžka (mm)	MS	SW (mm)
K- 07 40 39 58	G 1/8 female	15,0	29,5	4,3	14
K- 07 40 39 59	G 1/4 female	15,0	35,3	6,0	19
K- 07 40 39 60	G 3/8 female	15,0	39,0	7,5	22
K- 07 40 39 61	G 1/2 female	10,0	48,0	11,0	27
K- 07 40 39 62	G 3/4 female	10,0	60,0	13,0	36