

K-LKM 5 UWB

Non-interchangeable quick disconnect couplings DN 5

HANSA FLEX

Vlastnosti

Prevádzkový tlak	0 - 35 bar, maximum static working pressure (non-pulsating)
Prietok vzduch	560 l/min (at 6 bar and $\Delta p = 0.5$ bar)
Teplota média	-20 °C to +100 °C
uvoľňovacie puzdro	Anodised aluminium
pružina, rozperný krúžok, gule	stain less steel
Tesniaci materiál	NBR



Poznámka

Standard push-in plugs for couplings DN 5 and DN 7.2 – DN 7.8 are compatible with these non-interchangeable couplings.

Ďalšie údaje na vyžiadanie.

Popis

One-hand quick disconnect couplings with a large bore. Different media can be connected safely and non-interchangeably even when space is restricted, thanks to the colour-coded coupling and plug and the different coupling profiles defined for each of the four colours. Only couplings and plugs of the same colour fit together.

Výrobok

Označenie	Prípojka	Farba	Dĺžka (mm)	SW (mm)
K- 07 35 06 80	G 1/8 male	zelená	45,0	14
K- 07 35 06 81	G 1/4 male	zelená	47,0	17
K- 07 35 06 82	G 1/8 female	zelená	45,0	14
K- 07 35 06 83	G 1/4 female	zelená	47,0	17
K- 07 35 06 84	G 1/8 male	Brown	45,0	14
K- 07 35 06 85	G 1/4 male	Brown	47,0	17
K- 07 35 06 86	G 1/8 female	Brown	45,0	14
K- 07 35 06 87	G 1/4 female	Brown	47,0	17
K- 07 35 06 88	G 1/8 male	modrá	45,0	14
K- 07 35 06 89	G 1/4 male	modrá	47,0	17
K- 07 35 06 90	G 1/8 female	modrá	45,0	14
K- 07 35 06 91	G 1/4 female	modrá	47,0	17
K- 07 35 06 92	G 1/8 male	červená	45,0	14
K- 07 35 06 93	G 1/4 male	červená	47,0	17
K- 07 35 06 94	G 1/8 female	červená	45,0	14
K- 07 35 06 95	G 1/4 female	červená	47,0	17