K-LKM 7,8 UWB

Non-interchangeable quick disconnect couplings DN 7.8

Vlastnosti

Prevádzkový tlak	0 - 35 bar, maximum static working pressure (non-pulsating)
Prietok vzduch	1.800 l/min (at 6 bar and Δp = 0.5 bar)
Teplota média	-20 °C to +100 °C
Kryt	Brass
Ventil	Die-cast zinc, nickel-plated
uvoľňovacie puzdro	Anodised aluminium
pružina, rozperný krúžok, gule	stain less steel
Tesniaci materiál	NBR



Poznámka

Standard push-in plugs for couplings DN 5 and DN 7.2 – DN 7.8 are compatible with these non-interchangeable couplings.
Ďalšie údaje na vyžiadanie.

Popis

One-hand quick disconnect couplings with a large bore. Different media can be connected safely and non-interchangeably even when space is restricted, thanks to the colour-coded coupling and plug and the different coupling profiles defined for each of the four colours. Only couplings and plugs of the same colour fit together.

Výrobok

Označenie	Prípojka	Farba	Dĺžka (mm)	SW (mm)
K- 07 35 08 01	G 1/4 male	zelená	57,5	19
K- 07 35 08 02	G 3/8 male	zelená	57,5	19
K- 07 35 08 03	G 1/4 female	zelená	55,5	19
K- 07 35 08 04	G 3/8 female	zelená	54,5	19
K- 07 35 08 05	G 1/4 male	Brown	57,5	19
K- 07 35 08 06	G 3/8 male	Brown	57,5	19
K- 07 35 08 07	G 1/4 female	Brown	55,5	19
K- 07 35 08 08	G 3/8 female	Brown	54,5	19
K- 07 35 08 09	G 1/4 male	modrá	57,5	19
K- 07 35 08 10	G 3/8 male	modrá	57,5	19
K- 07 35 08 11	G 1/4 female	modrá	55,5	19
K- 07 35 08 12	G 3/8 female	modrá	54,5	19
K- 07 35 08 13	G 1/4 male	červená	57,5	19
K- 07 35 08 14	G 3/8 male	červená	57,5	19
K- 07 35 08 15	G 1/4 female	červená	55,5	19
K- 07 35 08 16	G 3/8 female	červená	54,5	19

Napriek čo najstarostlivejšej kontrole nemôžeme vylúčiť chyby a nepreberáme žiadnu záruku za zahrnuté údaje.