


K-LKS 7,8 UWB

Stems and plugs DN 7.8

HANSA FLEX

Vlastnosti

Prevádzkový tlak	0 - 35 bar, maximum static working pressure (non-pulsating)
Prietok vzduch	1.800 l/min (at 6 bar and $\Delta p = 0.5$ bar)
Teplota média	-20 °C to +100 °C
Materiál	Mosadz



Poznámka

Ďalšie údaje na vyžiadanie.

Výrobok

Označenie	Definícia	Farba	SW (mm)
K- 07 35 02 71	Stem, I.D. 6	zelená	-
K- 07 35 02 72	Stem, I.D. 9	zelená	-
K- 07 35 02 73	Stem, I.D. 6	Brown	-
K- 07 35 02 74	Stem, I.D. 9	Brown	-
K- 07 35 02 75	Stem, I.D. 6	modrá	-
K- 07 35 02 76	Stem, I.D. 9	modrá	-
K- 07 35 02 77	Stem, I.D. 6	červená	-
K- 07 35 02 78	Stem, I.D. 9	červená	-
K- 07 35 02 79	Plug G 1/4 male	zelená	17
K- 07 35 02 80	Plug G 3/8 male	zelená	19
K- 07 35 02 81	Plug G 1/4 male	Brown	17
K- 07 35 02 82	Plug G 3/8 male	Brown	19
K- 07 35 02 83	Plug G 1/4 male	modrá	17
K- 07 35 02 84	Plug G 3/8 male	modrá	19
K- 07 35 02 85	Plug G 1/4 male	červená	17
K- 07 35 02 86	Plug G 3/8 male	červená	19