

K-INLINE-EJEKTOREN VR

Inline ejectors »VR«, screw connection

HANSA FLEX

Vlastnosti


Vlastnosti Vacuum generator with high maximum vacuum level (85% vacuum)
No moving parts, which means no wear and no maintenance
ultra small footprint, suitable for confined spaces
minimal air consumption
Inlow noise

Použitie by screwing / plugging into the distribution beam direct attachment to the suction pad for handling various workpieces

Kryt Aluminium eloxed (type VR)

Systém trysiek Brass (type VR)

Prípojka Násuvná prípojka



Poznámka

Ďalšie údaje na vyžiadanie.

Popis

For vacuum generation directly at the point of use. For direct installation between the suction pad and the compressed air supply. Purely pneumatic vacuum generator that operates on the Venturi principle. Compressed air enters the ejector and flows through a nozzle. This results in a vacuum immediately behind the nozzle outlet, and air is drawn in through the vacuum inlet. This air and the driving air leave the ejector and enter the atmosphere via the exhaust air outlet.

Výrobok

Označenie	Veľkosť trysky	Prípojka odpadového vzduchu	Prípoj stlačeného vzduchu	Prípojenie vákua	Stupeň vákuovania	Spotreba vzduchu nasávania (L/min)	max. schopnosť nasávania (L/min)	Dĺžka (mm)	Prevádzkový tlak (bar)
K-07 45 01 29	0,7	M 5 male	G 1/4 IG	G1/8 female	90 %	21,0	14,0	35,0	5,0
K-07 45 01 30	0,9	M 5 male	G 1/4 IG	G1/8 female	89 %	36,0	21,0	35,0	5,0