K-FEDERSTOESSEL
Spring plungers

Vlastnosti

Použitie	Handling of workpieces with differing heights (eg. Curved metal sheets) Handling of very sensitive workpieces, very soft landing is assured
Teplota min.	0 °C
Teplota max.	80 °C
Prípoj nasávania	M 3 female
Vyhotovenie	Spring plunger with high-strength steel rodl, guide sleeve and lower damping spring Plunger rod with integrated vacuum guide
Dráha pružiny	5,0 mm



Poznámka
Ďalšie údaje na vyžiadanie.

Popis
Suitable for all round or oval suction pads in our standard range.

Výrobok

Označenie	Pripojenie vákua	Dĺžka (mm)	Vertikálne zaťaženie (N/m2)
K- 07 45 00 73	M 3 female	33,5	550
K- 07 45 00 76	M 5 female	41,2	1500
K- 07 45 00 74	M 5 female	47,2	1500
K- 07 45 00 75	M 5 female	59,2	1500
K- 07 45 00 70	G 1/8 female	80,0	3700
K- 07 45 00 67	G 1/8 female	95,0	3700
K- 07 45 00 71	G 1/8 female	93,0	3700
K- 07 45 00 68	G 1/8 female	124,5	2400
K- 07 45 00 72	G 1/8 female	124,0	2400
K- 07 45 00 69	G 1/8 female	154,0	2400

Napriek čo najstarostlivejšej kontrole nemôžeme vylúčiť chyby a nepreberáme žiadnu záruku za zahrnuté údaje.