

K-FEDERSTOESSEL

Spring plungers

HANSA FLEX

Vlastnosti

Použitie	Handling of workpieces with differing heights (eg. Curved metal sheets) Handling of very sensitive workpieces, very soft landing is assured
Teplota min.	0 °C
Teplota max.	80 °C
Prípoj nasávaní	M 3 female
Vyhotovenie	Spring plunger with high-strength steel rod, guide sleeve and lower damping spring Plunger rod with integrated vacuum guide
Dráha pružiny	5,0 mm



Poznámka

Ďalšie údaje na vyžiadanie.

Popis

Suitable for all round or oval suction pads in our standard range.

Výrobok

Označenie	Prípojenie váku	Dĺžka (mm)	Vertikálne zaťaženie (N/m ²)
K- 07 45 00 73	M 3 female	33,5	550
K- 07 45 00 76	M 5 female	41,2	1500
K- 07 45 00 74	M 5 female	47,2	1500
K- 07 45 00 75	M 5 female	59,2	1500
K- 07 45 00 70	G 1/8 female	80,0	3700
K- 07 45 00 67	G 1/8 female	95,0	3700
K- 07 45 00 71	G 1/8 female	93,0	3700
K- 07 45 00 68	G 1/8 female	124,5	2400
K- 07 45 00 72	G 1/8 female	124,0	2400
K- 07 45 00 69	G 1/8 female	154,0	2400