

K-DRS MDR 5 M ENTLASTU VENT

»MDR 5« pressure switches, with unloading valve / on/off switch / flange 1/4, without motor protection circuit

HANSA FLEX

Vlastnosti

Teplota média	-5 °C to +80 °C
max. vypínací tlak	16 bar
Schopnosť spínania	5,5 kW
Druh kontaktu	NC (3-pole)
max. frekvencia spínania	120 (electrical), 600 (mechanical)
Krytie	IP 54



Poznámka

G thread acc. to DIN EN ISO 228-1, with ISO flange plate (acc. to ISO 5211)
Ďalšie údaje na vyžiadanie.

Popis

Three-phase version

Pokyny pre objednanie

For use on devices that have to be vented whenever they are turned off, either because of safety regulations or for technical reasons. The pneumatic devices are disconnected from the system and simultaneously vented each time they are shut off.

Dodatočné informácie

Important: A thermal, 3-pole overcurrent relay must be ordered together with these switches. Without this relay, the on/off mechanism does not work.

Výrobok

Označenie	Prípoj stlačeného vzduchu	Rozsah nastavenia
K- 07 30 24 25	G 1/2	2,0 - 11,0 bar
K- 07 30 24 27	G 1/2	2,5 - 16,0 bar