

K-DRS STANDARD

Standard pressure switches

HANSA FLEX

Vlastnosti

Konštrukcia	Spring-loaded diaphragm (NBR); Spring-loaded piston; (10 to 70 bar versions)
Oblasť použitia	Air, hydraulic oil, oil emulsions, water
Teplota okolia	-25 °C to +85 °C
Elektrické pripojenie	Tab connectors 2 x 6.3 x 0.8
Frekvencia spínania	200/min.
Spínacie napätie	42 V
Materiál	Galvanised steel



Poznámka

Ďalšie údaje na vyžiadanie.

Popis

For liquid, non-corrosive and gaseous media. Easy to adjust, even under pressure. Can be integrated in any mounting position. Pressure adjustment by means of a hexagon-head screw.

Výrobok

Označenie	Závit	Rozsah nastavenia	funkcia
K- 07 30 24 94	G 1/8	0,3 - 2,0 bar	closer
K- 07 30 24 95	G 1/8	1,0 - 10,0 bar	closer
K- 07 30 24 96	G 1/8	10,0 - 70,0 bar	closer
K- 07 30 24 97	G 1/4	0,3 - 2,0 bar	closer
K- 07 30 24 98	G 1/4	1,0 - 10,0 bar	closer
K- 07 30 24 99	G 1/4	10,0 - 70,0 bar	closer
K- 07 30 24 10	G 1/8	0,3 - 2,0 bar	opener
K- 07 30 24 11	G 1/8	1,0 - 10,0 bar	opener
K- 07 30 24 12	G 1/8	10,0 - 70,0 bar	opener
K- 07 30 24 13	G 1/4	0,3 - 2,0 bar	opener
K- 07 30 24 14	G 1/4	1,0 - 10,0 bar	opener
K- 07 30 24 15	G 1/4	10,0 - 70,0 bar	opener