

K-DRS W WECHSELKONTAKT ANFLANSCHB^{AD}

Pressure switches changeover type, flange mounting

HANSA FLEX

Vlastnosti

| | |
|-----------------------|---|
| Konštrukcia | Spring-loaded diaphragm (NBR) |
| Oblasť použitia | Air, neutral gases (lubricated or unlubricated) |
| Teplota okolia | -25 °C to +85 °C |
| Elektrické pripojenie | Coupling plug PG 11 P nach ISO 4400 |
| Frekvencia spínania | 60/min. |
| Spínacie napätie | max. 250 V AC/DC |
| Funkcia | Changeover |
| Materiál | to 10 bar: plastic Grivory (PA 61/XT) bzw.; to 16 bar: Alu black eloxed |



Poznámka

Ďalšie údaje na vyžiadanie.

Popis

Special pressure switches for pneumatic applications. Extremely precise thanks to the large control diaphragm. Two through holes in the housing for flanging the switch.

Výrobok

| Označenie | Závit | Rozsah nastavenia |
|----------------|-------|-------------------|
| K- 07 30 28 42 | G 1/4 | 0,2 - 6,0 bar |
| K- 07 30 28 43 | G 1/4 | 0,5 - 10,0 bar |
| K- 07 30 28 44 | G 1/4 | 0,5 - 16,0 bar |