

# K-DRS W WECHSELKONTAKT ANFLANSCHB<sup>AD</sup>

Pressure switches changeover type, flange mounting

**HANSA FLEX**

## Vlastnosti

|                       |   |
|-----------------------|---|
| Konštrukcia           | Spring-loaded diaphragm (NBR)   |
| Oblasť použitia       | Air, neutral gases (lubricated or unlubricated)                         |
| Teplota okolia        | -25 °C to +85 °C  |
| Elektrické pripojenie | Coupling plug PG 11 P nach ISO 4400                                     |
| Frekvencia spínania   | 60/min.   |
| Spínacie napätie      | max. 250 V AC/DC  |
| Funkcia               | Changeover  |
| Materiál              | to 10 bar: plastic Grivory (PA 61/XT) bzw.; to 16 bar: Alu black eloxed |



## Poznámka

Ďalšie údaje na vyžiadanie.

## Popis

Special pressure switches for pneumatic applications. Extremely precise thanks to the large control diaphragm. Two through holes in the housing for flanging the switch.

## Výrobok

| Označenie      | Závit | Rozsah nastavenia |
|----------------|-------|-------------------|
| K- 07 30 28 42 | G 1/4 | 0,2 - 6,0 bar     |
| K- 07 30 28 43 | G 1/4 | 0,5 - 10,0 bar    |
| K- 07 30 28 44 | G 1/4 | 0,5 - 16,0 bar    |