

K-DRS W BAJONETT

Pressure switches - changeover type

Vlastnosti

Konštrukcia	Spring-loaded diaphragm (UR); Spring-loaded piston; (10 to 70 bar versions)
Teplota okolia	-25 °C to +85 °C
Elektrické pripojenie	Bayonet coupling connector Ø 2.5 mm
Frekvencia spínania	200/min.
Menovité napätie	42 V
Funkcia	Changeover
Materiál	Galvanised steel



Poznámka

Ďalšie údaje na vyžiadanie.

Popis

Special pressure switches for critical (water) or outdoor applications. Maximum degree of protection IP67 when a bayonet coupling is used for the electrical connection.

Výrobok

Označenie	Závit	Rozsah nastavenia
K- 07 30 28 36	G 1/8	0,5 - 2,0 bar
K- 07 30 28 37	G 1/8	1,0 - 10,0 bar
K- 07 30 28 38	G 1/8	10,0 - 70,0 bar
K- 07 30 28 39	G 1/4	0,5 - 2,0 bar
K- 07 30 28 40	G 1/4	1,0 - 10,0 bar
K- 07 30 28 41	G 1/4	10,0 - 70,0 bar

Príslušenstvo

K-WECHSELKONTAKT BANJOETT Changeover type bayonet coupling