

# K-BKR LEICHT IG AG

Ball valves, lightweight type, female/male thread

**HANSA FLEX**

## Vlastnosti

<b>Oblasť použitia</b>	Compressed air, water, non-toxic and non-corrosive gases, heating systems, agriculture
<b>Prevádzkový tlak</b>	Max. 40 bar
<b>Prevádzková teplota</b>	-15 °C to +90 °C
<b>Popis závitů</b>	G thread acc. DIN EN ISO 228-1
<b>Kryt</b>	Nickel-plated brass
<b>páka</b>	Alu, painted black
<b>guľa</b>	Chrome-plated brass
<b>Tesnenie gule</b>	PTFE
<b>Tesnenie vretena</b>	HNBR / EPDM / PTFE. 2 O-Rings (HNBR / EPDM) 1 gasket (PTFE) additional PTFE-gasket



## Poznámka

Ďalšie údaje na vyžiadanie.

## Výrobok

Označenie	DN	Závit	A: (mm)	B (mm)	D (mm)
K- 07 30 00 25	8	G 1/4	85,0	42,0	44,0
K- 07 30 00 26	10	G 3/8	85,0	42,0	51,0
K- 07 30 00 27	15	G 1/2	85,0	46,0	60,0
K- 07 30 00 28	20	G 3/4	105,0	53,0	70,0
K- 07 30 00 29	25	G 1	105,0	57,0	79,0
K- 07 30 00 30	32	G 1 1/4	130,0	70,0	91,0
K- 07 30 00 31	40	G 1 1/2	130,0	76,0	104,0
K- 07 30 00 32	50	G 2	165,0	92,0	122,0