

# K-MV G 230 V, 50 - 60 HZ D

Normally closed, 230 V, 50 to 60 Hz, directly operated

**HANSA FLEX**

## Vlastnosti

<b>Elektrické pripojenie</b>	For Pg 11P connector socket, acc. to DIN 4400
<b>Krytie</b>	IP65 (with connector socket fitted)
<b>Teplota média</b>	max. +90 °C with Perbunan-seal; max. +130 °C with FKM-Seal
<b>kryt, sedlo ventíla</b>	Stainless steel
<b>vnútorné diely</b>	Stainless steel
<b>tesnenie</b>	Perbunan (NBR) or FKM



## Poznámka

Ďalšie údaje na vyžiadanie.

## Popis

Available versions, Directly operated, Combined operation

## Výrobok

Označenie	Závit	max. prevádzkový tlak (bar)	MS	Tesniaci materiál	A: (mm)	B: (mm)	vyhotovenie
K- 07 30 22 46	G 1/8	20	2,4	NBR	80,0	30,0	1
K- 07 30 22 48	G 1/8	20	2,4	FKM	80,0	30,0	1
K- 07 30 22 47	G 1/4	12	4,0	NBR	85,0	45,0	1
K- 07 30 22 49	G 1/4	12	4,0	FKM	85,0	45,0	1