


# K-MV G 24 V DC D

Normally closed, 24 V DC (direct current), directly operated

**HANSA FLEX**

## Vlastnosti

<b>Elektrické pripojenie</b>	For Pg 11P connector socket, acc. to DIN 4400
<b>Krytie</b>	IP65 (with connector socket fitted)
<b>Teplota média</b>	max. +90 °C with Perbunan-seal; max. +130 °C with FKM-Seal
<b>kryt, sedlo ventíla</b>	Stainless steel
<b>vnútorné diely</b>	Stainless steel
<b>tesnenie</b>	Perbunan (NBR) or FKM



## Poznámka

Ďalšie údaje na vyžiadanie.

## Popis

Available versions, Directly operated, Combined operation

## Výrobok

Označenie	Závit	max. prevádzkový tlak (bar)	MS	Tesniaci materiál	A: (mm)	B (mm)	vyhotovenie
K- 07 30 23 18	G 1/8	10	2,4	NBR	80,0	30,0	1
K- 07 30 23 20	NPT 1/8	10	2,4	FKM	80,0	30,0	1
K- 07 30 23 19	G 1/4	3	4,0	NBR	80,0	45,0	1
K- 07 30 23 21	G 1/4	3	4,0	FKM	80,0	45,0	1