


K-MV G 24 V DC D

Normally closed, 24 V DC (direct current), directly operated

HANSA FLEX

Vlastnosti

| | |
|------------------------------|--|
| Elektrické pripojenie | For Pg 11P connector socket, acc. to DIN 4400 |
| Krytie | IP65 (with connector socket fitted) |
| Teplota média | max. +90 °C with Perbunan-seal; max. +130 °C with FKM-Seal |
| kryt, sedlo ventíla | Stainless steel |
| vnútorné diely | Stainless steel |
| tesnenie | Perbunan (NBR) or FKM |



Poznámka

Ďalšie údaje na vyžiadanie.

Popis

Available versions, Directly operated, Combined operation

Výrobok

| Označenie | Závit | max. prevádzkový tlak (bar) | MS | Tesniaci materiál | A: (mm) | B (mm) | vyhotovenie |
|----------------|---------|--------------------------------|-----|-------------------|------------|-----------|-------------|
| K- 07 30 23 18 | G 1/8 | 10 | 2,4 | NBR | 80,0 | 30,0 | 1 |
| K- 07 30 23 20 | NPT 1/8 | 10 | 2,4 | FKM | 80,0 | 30,0 | 1 |
| K- 07 30 23 19 | G 1/4 | 3 | 4,0 | NBR | 80,0 | 45,0 | 1 |
| K- 07 30 23 21 | G 1/4 | 3 | 4,0 | FKM | 80,0 | 45,0 | 1 |