


# K-MV G D 24 V DC

Normally closed, directly operated, 24 V DC (direct current)

**HANSA FLEX**

## Vlastnosti

Elektrické pripojenie	ISO 4400. cable socket (Pg 11P)
Krytie	IP65 (with connector socket fitted)
Teplota média	max. +80 °C with Perbunan-seal; max. +130 °C with FKM-Seal
Popis závitů	G-thread acc. to DIN EN ISO 228-1, Rp-thread acc. to ISO 7-1
kryt, sedlo ventila	Brass
vnútorne diely	Stainless steel
tesnenie	Perbunan (NBR) or FKM



## Poznámka

Ďalšie údaje na vyžiadanie.

## Popis

Standard series, proven over many years, available in three different versions: Directly operated, Combined operation, Pilot-operated. For all applications with compressed air, neutral gases or low-viscosity, neutral media.

## Výrobok

Označenie	Závit	max. prevádzkový tlak (bar)	MS	Tesniaci materiál	A: (mm)	B: (mm)	vyhotovenie
K- 07 30 23 08	G 1/8	5	3,2	NBR	75,0	30,0	1
K- 07 30 23 10	G 1/8	5	3,2	FKM	75,0	30,0	1
K- 07 30 23 09	G 1/4	4	3,2	NBR	75,0	40,0	2
K- 07 30 23 11	G 1/4	4	3,2	FKM	75,0	40,0	2