


K-MV O Z 24 V DC

Normally open, combined operation, 24 V DC (direct current)

HANSA FLEX

Vlastnosti

Elektrické pripojenie	ISO 4400. cable socket (Pg 11P)
Krytie	IP65 (with connector socket fitted)
Teplota média	max. +80 °C with Perbunan-seal; max. +130 °C with FKM-Seal
Popis závitů	G-thread acc. to DIN EN ISO 228-1, Rp-thread acc. to ISO 7-1
kryt, sedlo ventilu	Brass
vnútorné diely	Stainless steel
tesnenie	Perbunan (NBR) or FKM



Poznámka

Ďalšie údaje na vyžiadanie.

Popis

Standard series, proven over many years, available in three different versions: Directly operated, Combined operation, Pilot-operated. For all applications with compressed air, neutral gases or low-viscosity, neutral media.

Výrobok

Označenie	Závit	max. prevádzkový tlak (bar)	MS	Tesniaci materiál	A: (mm)	B: (mm)	vyhotovenie
K- 07 30 24 00	Rp 3/8	9	16,0	NBR	80,0	70,0	3
K- 07 30 24 01	Rp 1/2	9	16,0	NBR	80,0	70,0	3
K- 07 30 24 02	Rp 3/4	9	19,0	NBR	80,0	70,0	3