

# K-ABBLV 1

Blow-off safety valves G 1/8

**HANSA FLEX**

## Vlastnosti

|                     |              |
|---------------------|--------------|
| Prevádzkový tlak    | 0.5 - 60 bar |
| Prevádzková teplota | max. 180 °C  |
| Tesnenia            | FKM          |
| Kryt                | Brass        |



## Poznámka

G thread acc. to DIN EN ISO 228-1, with ISO flange plate (acc. to ISO 5211)

Ďalšie údaje na vyžiadanie.

## Popis

Manual adjustment of the blow-off pressure (lock nut).

## Pokyny pre objednanie

For use on devices that have to be vented whenever they are turned off, either because of safety regulations or for technical reasons. The pneumatic devices are disconnected from the system and simultaneously vented each time they are shut off.

## Dodatočné informácie

These blow-off valves can also be supplied with a fixed setting and a TÜV type test number. Please ask for an offer.

## Výrobok

| Označenie      | Závit | Reakčný tlak    | Výkon vyfukovania | C<br>(mm) | D:<br>(mm) | do<br>(mm) | SW<br>(mm) |
|----------------|-------|-----------------|-------------------|-----------|------------|------------|------------|
| K- 07 30 29 17 | G 1/8 | 0.5 - 1.0 bar   | to 50 l/min       | 27,0      | 7,0        | 3,0        | 16         |
| K- 07 30 21 89 | G 1/8 | 1.0 - 4.0 bar   | to 200 l/min      | 27,0      | 7,0        | 3,0        | 16         |
| K- 07 30 21 90 | G 1/8 | 3.0 - 7.0 bar   | to 350 l/min      | 27,0      | 7,0        | 3,0        | 16         |
| K- 07 30 21 91 | G 1/8 | 6.0 - 12.0 bar  | to 650 l/min      | 27,0      | 7,0        | 3,0        | 16         |
| K- 07 30 21 92 | G 1/8 | 10.0 - 18.0 bar | to 870 l/min      | 27,0      | 7,0        | 3,0        | 16         |
| K- 07 30 21 93 | G 1/8 | 16.0 - 32.0 bar | to 1600 l/min     | 27,0      | 7,0        | 3,0        | 16         |
| K- 07 30 21 94 | G 1/8 | 30.0 - 60.0 bar | to 3000 l/min     | 27,0      | 7,0        | 3,0        | 16         |