

K-VERSCHLUSSKAPPEN 6KT U. 8KT

Caps, hexagonal (G 3/4 to G 2 = octagon)

HANSA FLEX

Vlastnosti

| | |
|----------------|------------------------------|
| Pracovný tlak | Max. 20 bar |
| vnútorný závit | Parallel to DIN EN ISO 228-1 |
| Materiál | Stainless steel 1.4408 |



Poznámka

The dimensions of the standard screw fittings may change slightly during the life of the catalogue as a result of optimisation processes.

Ďalšie údaje na vyžiadanie.

Výrobok

| Označenie | Závit | L1 (mm) | SW |
|----------------|---------|------------|-------|
| K- 07 40 39 40 | G 1/8 | 15,5 | 13 mm |
| K- 07 40 39 41 | G 1/4 | 16,0 | 16 mm |
| K- 07 40 39 42 | G 3/8 | 18,0 | 20 mm |
| K- 07 40 39 43 | G 1/2 | 22,6 | 26 mm |
| K- 07 40 39 44 | G 3/4 | 25,0 | 32 mm |
| K- 07 40 39 45 | G 1 | 30,0 | 40 mm |
| K- 07 40 39 46 | G 1 1/4 | 31,0 | 48 mm |
| K- 07 40 39 47 | G 1 1/2 | 33,0 | 56 mm |
| K- 07 40 39 48 | G 2 | 36,0 | 66 mm |