

# K-W90 DERH AG 1

Male elbows, swivel type, parallel male thread

**HANSA FLEX**

## Vlastnosti

|                     |  |
|---------------------|--|
| Prevádzkový tlak    | Max. 16 bar (at +20 °C)                      |
| Prevádzková teplota | -20 °C to +70 °C                             |
| Materiál            | Mosadzný poniklovaný                         |
| Prítláčny krúžok    | Hostaform (black nickel-plated for Ø 10, 12) |
| O-krúžok            | NBR, siliconefree                            |
| napínacie kliešte   | Stainless steel AISI 316                     |



## Poznámka

Ďalšie údaje na vyžiadanie.

## Popis

Economy yet very high-quality series of push-in fittings made of nickel-plated brass. Compact, space-saving, lightweight design. An O-ring in the fillet at the end of the thread guarantees a tight connection for all male thread parts, even on rough surfaces.

## Výrobok

| Označenie      | Závit | pre vonkajší Ø hadice | L1<br>(mm) | L2<br>(mm) | SW    |
|----------------|-------|-----------------------|------------|------------|-------|
| K- 07 40 29 68 | M 5   | 4 mm                  | 19,0       | 14,5       | 9 mm  |
| K- 07 40 29 69 | M 5   | 6 mm                  | 21,0       | 14,5       | 9 mm  |
| K- 07 40 29 76 | G 1/8 | 4 mm                  | 19,0       | 20,0       | 13 mm |
| K- 07 40 29 77 | G 1/8 | 6 mm                  | 21,0       | 20,0       | 13 mm |
| K- 07 40 29 78 | G 1/8 | 8 mm                  | 24,0       | 20,0       | 13 mm |
| K- 07 40 29 73 | G 1/4 | 4 mm                  | 19,0       | 24,0       | 13 mm |
| K- 07 40 29 74 | G 1/4 | 6 mm                  | 21,0       | 24,0       | 13 mm |
| K- 07 40 29 75 | G 1/4 | 8 mm                  | 24,0       | 24,0       | 13 mm |
| K- 07 40 29 72 | G 1/4 | 10 mm                 | 27,0       | 24,0       | 16 mm |
| K- 07 40 29 81 | G 3/8 | 8 mm                  | 24,0       | 25,5       | 13 mm |
| K- 07 40 29 79 | G 3/8 | 10 mm                 | 27,0       | 28,0       | 16 mm |
| K- 07 40 29 80 | G 3/8 | 12 mm                 | 28,0       | 28,5       | 20 mm |
| K- 07 40 29 70 | G 1/2 | 10 mm                 | 27,0       | 30,0       | 16 mm |
| K- 07 40 29 71 | G 1/2 | 12 mm                 | 28,0       | 33,5       | 20 mm |