

# K-DOPPELNIPPEL AG-K MS

Detachable double nipples brass

**HANSA FLEX**

## Vlastnosti

|                |                                 |
|----------------|---------------------------------|
| Pracovný tlak  | 10 bar                          |
| Teplota média  | max. +90 °C                     |
| Teplota okolia | Max. +90 °C                     |
| Materiál       | Brass with a bare metal surface |



## Poznámka

The dimensions of the standard screw fittings may change slightly during the life of the catalogue as a result of optimisation processes.  
Ďalšie údaje na vyžiadanie.

## Dodatočné informácie

Further types and dimensions on request.

## Výrobok

| Označenie      | Závit 1 | Závit 2 | L1<br>(mm) | SW    | SW1<br>(mm) |
|----------------|---------|---------|------------|-------|-------------|
| K- 07 40 00 33 | R 1/8   | R 1/8   | 27,0       | 15 mm | 5           |
| K- 07 40 00 39 | R 1/8   | R 1/4   | 30,0       | 15 mm | 5           |
| K- 07 40 00 34 | R 1/4   | R 1/4   | 33,5       | 19 mm | 6           |
| K- 07 40 00 40 | R 1/4   | R 3/8   | 34,5       | 19 mm | 6           |
| K- 07 40 00 35 | R 3/8   | R 3/8   | 36,5       | 22 mm | 8           |
| K- 07 40 00 36 | R 1/2   | R 1/2   | 44,0       | 27 mm | 12          |
| K- 07 40 00 37 | R 3/4   | R 3/4   | 53,0       | 36 mm | 14          |
| K- 07 40 00 38 | R 1     | R 1     | 63,5       | 46 mm | 19          |