

# K-DOPPELNIPPEL AG-K MS

Detachable double nipples brass

**HANSA FLEX**

## Vlastnosti

Pracovný tlak	10 bar
Teplota média	max. +90 °C
Teplota okolia	Max. +90 °C
Materiál	Brass with a bare metal surface



## Poznámka

The dimensions of the standard screw fittings may change slightly during the life of the catalogue as a result of optimisation processes.  
Ďalšie údaje na vyžiadanie.

## Dodatočné informácie

Further types and dimensions on request.

## Výrobok

Označenie	Závit 1	Závit 2	L1 (mm)	SW	SW1 (mm)
K- 07 40 00 33	R 1/8	R 1/8	27,0	15 mm	5
K- 07 40 00 39	R 1/8	R 1/4	30,0	15 mm	5
K- 07 40 00 34	R 1/4	R 1/4	33,5	19 mm	6
K- 07 40 00 40	R 1/4	R 3/8	34,5	19 mm	6
K- 07 40 00 35	R 3/8	R 3/8	36,5	22 mm	8
K- 07 40 00 36	R 1/2	R 1/2	44,0	27 mm	12
K- 07 40 00 37	R 3/4	R 3/4	53,0	36 mm	14
K- 07 40 00 38	R 1	R 1	63,5	46 mm	19